

Out of Band Authentication Adapter

Adapter Loading Process

The ActiveAccess ACS performs Out Of Band (OOB) challenges through OOB Adapters, which connect the existing OOB authentication system with ActiveAccess. During 3DSecure 2.0 challenge flows where OOB Authentication is required, the ACS will trigger the external OOB process and perform interactions with the Cardholder via the OOB Adapters.

For this purpose, the ACS communicates with the existing OOB-System via a middleware, known as the OOB Adapter. The OOB Adapter can be either loaded locally by the ACS or communicated via HTTP calls, known as the Native API and REST API versions respectively.

Native API version of OOB Adapter

The Native API version of OOB Adapter is known as `oob.adapter` in this specification. The Native Adapters are provided in the form of `JAR` files, by GPayments or ActiveAccess clients. Only Java is supported for the Native API version of OOB Adapter.

Native OOB Adapter developers provide the adapters in one or more JAR files. The `oob.adapter` implementation in the adapter must implement the Java interface `Adapter` in the `com.gpayments.oob.api.v1` package.

Implementation Steps

The steps for implementing OOB Adapter are:

1. OOB Adapter developers create a Java project and obtain the corresponding Adapter API library from the ActiveAccess package. This library contains the interface definition for `oob.adapter` (Native OOB Adapter).
2. The Native API Adapter should be implemented as a Service based on the OOB interface `Adapter`. This specific implementation of the service known as *service provider*. ACS loads this class in startup and uses it in OOB Authentication. The requirement enforced by ACS is that *provider class* must have a public zero-argument constructor so that it can be instantiated during loading.

3. A service provider is identified by placing a *provider-configuration file* in the resource directory `META-INF/services`. The file's name is the fully-qualified binary name of the service's type, e.g. `com.gpayments.oob.api.v1.Adapter`. The file contains a list of fully-qualified binary names of concrete provider classes, one per line. Space and tab characters surrounding each name, as well as blank lines, are ignored. The comment character is '#' ('\\u0023', NUMBER SIGN); on each line all characters following the first comment character are ignored. The file must be encoded in `UTF-8`.

Adapter Interface Methods

The `Adapter` interface has four methods as follows:

- **Method Name:** `getAdapterInfo`
 - **Description:** Returns information about `oob.adapter`
 - **Input:** This method takes no arguments
 - **Output:** An instance of `AdapterInfo` class that contains information about `oob.adapter` should be returned. The `AdapterInfo` is explained in detail in the [AdapterInfo Data Elements](#) section.
- **Method Name:** `ping`
 - **Description:** Checks whether OOB-Authenticator Server is accessible or not
 - **Input:** This method takes no arguments
 - **Output:** The result of OOB Server pinging should be returned in a *boolean* value. If the server responds to *ping* successfully, `true` should be returned, otherwise `false` should be returned.
- **Method Name:** `requestChallenge`
 - **Description:** To call when OOB authentication is necessary and returns whether authentication method for the card is available or not.
 - **Input:** This method takes the following parameters:
 - **Field Name:** `acsTransactionId`
 - **Description:** Universally Unique identifier assigned by the `ACS` to identify a single transaction
 - **Length:** 36 characters
 - **Format:** String

- **Accepted Value:** Canonical format as defined in IETF RFC 4122
- **Message Inclusion:** Required
- **Field Name:** `transactionInfo`
 - **Description:** Information about the transaction, which is required for the OOB authentication
 - **Length:**
 - **Format:** An instance of type `TransactionInfo`. `TransactionInfo` is explained in detail in the [TransactionInfo Data Elements](#) section.
 - **Accepted Value:**
 - **Message Inclusion:** Required
- **Output:** Adapter `requestChallenge` method has a `OobRequestChallengeResult` return type
 - **Field Name:** `oobRequestChallengeResult`
 - **Description:**
 - **Length:**
 - **Format:** An instance of type `OobRequestChallengeResult`. `OobRequestChallengeResult` is explained in details in the [OobRequestChallengeResult Data Elements](#) section.
 - **Accepted Value:**
 - **Message Inclusion:** Required
- **Method Name:** `getChallengeResult`
 - **Description:** Checks if the card is authenticated successfully or not
 - **Input:** This method takes the following parameters:
 - **Field Name:** `acsTransactionId`
 - **Description:** Universally Unique identifier assigned by the `ACS` to identify a single transaction.
 - **Length:** 36 characters
 - **Format:** String
 - **Accepted Value:** Canonical format as defined in IETF RFC 4122
 - **Message Inclusion:** Required

- **Field Name:** `oobTransId`
 - **Description:** Unique identifier assigned by the `OOB-Authenticator-System` to identify a single OOB Authentication Challenge
 - **Length:** Variable, maximum 36 characters.
 - **Format:** String
 - **Accepted Value:**
 - **Message Inclusion:** Optional
 - **Field Name:** `additionalInfo`
 - **Description:** Some additional Information for OOB authentication
 - **Length:**
 - **Format:** JSON object of `AdditionalInfo` type. `AdditionalInfo` is explained in the [AdditionalInfo Data Elements](#) section.
 - **Accepted Value:**
 - **Message Inclusion:** Optional
 - **Output:** Adapter `getChallengeResult` method has a `OobAuthenticationResult` return type.
 - **Field Name:** `oobAuthenticationResult`
 - **Description:**
 - **Length:**
 - **Format:** An instance of type `OobAuthenticationResult`. `OobAuthenticationResult` is explained in details in the [OobAuthenticationResult Data Elements](#) section.
 - **Accepted Value:**
 - **Message Inclusion:** Required
-

RESTful API version of OOB Adapter

For the Restful API version of the `oob.adapter`, a Restful API needs to be defined similar to the adapter interface. `ACS` implements the Restful client and the `OOB Adapter API Server` will be implemented by the client. In this case, no JARs or plugins need to be loaded by `ACS`. Clients

must provide a specific URL for **ACS** . Known as **Adapter-URL** in this document and the required REST API endpoints are defined based on this URL.

 Note

We also provide a Swagger API for the sample REST OOB Adapter server that is included in release package. To use it, run OOB Server in the installation package and then open `https://localhost:8447/swagger-ui.html#/` in your browser.

Get OOB Adapter Information

The ACS sends an HTTP request to get **oob.adapter** information. The details of this request are:

- **URL:** **Adapter-URL** /adapter-info
- **Request Method:** GET
- **Request Parameters:** there are not any request parameters for this REST API
- **Response:**
 - **Name:** adapterInfo
 - **Format:** JSON object of **AdapterInfo** .
 - **Description:** For further details on **AdapterInfo** , refer to the [AdapterInfo Data Elements](#) section.
 - **Inclusion:** Required

 Sample request

HTTP URL: `http://localhost:8447/restful-adapter/oob/adapter-info`

 Sample response

```
{
  "id": "0b99b82f-62cf-4275-88b3-de039020f14e",
  "name": "restful-adapter",
  "version": "1",
  "signature": "SIGNATURE"
}
```

Check OOB Authenticator Server availability status

The ACS sends an HTTP request to check whether OOB Authenticator Server is accessible or not. The details of this request are:

- **URL:** `Adapter-URL /ping`
- **Request Method:** GET
- **Request Parameters:** there are not any request parameters for this REST API
- **Response:** If Adapter Server is accessible to perform the OOB challenge process, this API returns an HTTP entity with 200 (OK) HTTP status code.

Request OOB Challenge

ACS calls an HTTP API when OOB authentication is necessary and returns whether authentication method for the card is available or not.

- **URL:** `Adapter-URL /request-challenge/{acsTransactionId}`
- **Request Method:** POST
- **Path variables:**
 - **Name:** acsTransactionId
 - **Format:** String
 - **Inclusion:** required
- **Request Body:**
 - **Name:** transactionInfo
 - **Format:** JSON object of TransactionInfo type. For further details on TransactionInfo, refer to the [TransactionInfo Data Elements](#) section.
 - **Inclusion:** required
- **Response:**
 - **Name:** oobRequestChallengeResult
 - **Format:** JSON object of OobRequestChallengeResult.
 - **Description:** `OobRequestChallengeResult` is explained in details in the [OobRequestChallengeResult Data Elements](#) section.
 - **Inclusion:** required

 Sample Request

HTTP URL: `http://localhost:8447/restful-adapter/oob/request-challenge/da3cb8f9-90a2-489b-a7af-28ba33ce924a`

```
Body: {
  "acctNumber": 4548812049400004,
  "additionalInfo": {
    "clientId": "123456789012345",
    "deviceId": "123e4567-e89b-12d3-a456-426655440000"
  },
  "cardHolderInfo": {
    "cardholderName": "cardholderName",
    "email": "abc@example.com",
    "homePhone": {
      "cc": 61,
      "subscriber": 234567890
    },
    "mobilePhone": {
      "cc": 61,
      "subscriber": 234567890
    },
    "shipAddrCity": "shipAddrCity",
    "shipAddrCountry": "040",
    "shipAddrLine1": "shipAddrLine1",
    "shipAddrLine2": "shipAddrLine2",
    "shipAddrLine3": "shipAddrLine3",
    "shipAddrPostCode": "shipAddrPostCode",
    "shipAddrState": "VIC",
    "workPhone": {
      "cc": 61,
      "subscriber": 234567890
    }
  },
  "deviceChannel": "01",
  "issuerName": "AnyBank",
  "merchantName": "merchantName",
  "messageCategory": "01",
  "purchaseAmount": 12345,
  "purchaseCurrency": "036",
  "purchaseExponent": 2,
  "threeDSServerTransID": "a4edc97f-4b89-4e52-8590-6c328f0b9648"
}
```

 Sample response

```
{
  "requestChallengeEnum": "OK",
  "oobTransId": "0679cb73-ea9a-41fb-8fda-dec78a46cd0b",
  "message": null
}
```

Get OOB authentication result

ACS calls an HTTP API to check if the cardholder is authenticated successfully or not. The details of this REST API are:

- **URL:** **Adapter-URL** /challenge-result/{acsTransactionId}/{oobTransId} (or **Adapter-URL** /challenge-result/{acsTransactionId} if **oobTransId** is null.)
- **Request Method:** POST
- **Path variables:**
 - **Name:** acsTransactionId
 - **Format:** String
 - **Inclusion:** Required
 - **Name:** oobTransId
 - **Format:** String
 - **Inclusion:** Optional
- **Request Body:**
 - **Name:** additionalInfo
 - **Format:** JSON object of **AdditionalInfo** type. You can find details of **AdditionalInfo** in the [AdditionalInfo Data Elements](#) section.
- **Response:**
 - **Name:** oobAuthenticationResult
 - **Format:** JSON object of type **OobAuthenticationResult**
 - **Description:** **OobAuthenticationResult** is explained in details in the [OobAuthenticationResult Data Elements](#) section.
 - **Inclusion:** Required

Authentication mechanism for the RESTful API version

Certificate based mutual authentication is used as the authentication mechanism for the RESTful API version. The steps are:

- **ACS** publishes a CA for adapter communication, known as **Adapter CA**
- **ACS** also issues a server certificate for the adapter.

- **ACS** uses a generated client certificate that is issued by the same **Adapter CA**.
 - The Adapter server implementation must be set up with the CA and mutual authentication provided.
 - **ACS** will try to connect to the Adapter Server and if the connection can be established then **ACS** will continue with the adapter, otherwise it throws an error.
-

Adapter Data Elements

AdapterInfo Data Elements

- **Field Name:** **id**
 - **Description:** The **ACS** assigned *UUID* to the **00B Adapter**
 - **Length:** 36 characters
 - **Format:** String
 - **Accepted Value:** Canonical format as defined in IETF RFC 4122
 - **Message Inclusion:** Required
- **Field Name:** **name**
 - **Description:** The **ACS** assigned *name* to the **00B Adapter**
 - **Length:** Variable, maximum 100 characters
 - **Format:** String
 - **Accepted Value:**
 - **Message Inclusion:** Required
- **Field Name:** **version**
 - **Description:** The number that indicates the **00B Adapter** version
 - **Length:** Variable
 - **Format:** String
 - **Accepted Value:**
 - **Message Inclusion:** Required
- **Field Name:** **signature**

 Note

This field is not currently used and is reserved for for future versions.

- **Description:** Signature to validate **OOB Adapter** integrity
- **Length:** Variable
- **Format:** String
- **Accepted Value:**
- **Message Inclusion:** Optional

TransactionInfo Data Elements

- **Field Name:** **threeDSServerTransID**

- **Description:** Universally unique transaction identifier assigned by the 3DS Server to identify a single transaction.
- **Length:** 36 characters
- **Format:** String
- **Accepted Value:** Canonical format as defined in IETF RFC 4122. May utilise any of the specified versions if the output meets specified requirements.
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Required

- **Field Name:** **additionalInfo**

- **Description:** Some additional Info for OOB authentication
- **Length:**
- **Format:** JSON object of **AdditionalInfo** type. **AdditionalInfo** is explained in the [AdditionalInfo Data Elements](#) section.
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

• **Field Name:** `purchaseAmount`

- **Description:** Purchase amount in minor units of currency with all punctuation removed. When used in conjunction with the Purchase Currency Exponent field, proper punctuation can be calculated.
- **Length:** 48 characters
- **Format:** String
- **Accepted Value:** Example: If the purchase amount is USD 123.45, element will contain the value 12345.
- **Device Channel:** 01-APP, 02-BRW
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** 01-PA: Required, 02-NPA: Conditional
- **Conditional Inclusion:** Required for 02NPA if 3DS Requestor Authentication Indicator = 02 or 03.

• **Field Name:** `purchaseCurrency`

- **Description:** Currency in which purchase amount is expressed.
- **Length:** 3 characters
- **Format:** String
- **Accepted Value:** ISO 4217 three-digit currency code; 955-964 and 999 values are excluded and not permitted.
- **Device Channel:** 01-APP, 02-BRW
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** 01-PA: Required, 02-NPA: Conditional
- **Conditional Inclusion:** Required for 02NPA if 3DS Requestor Authentication Indicator = 02 or 03.

• **Field Name:** `purchaseExponent`

- **Description:** Minor units of currency as specified in the ISO 4217 currency exponent.
- **Length:** 1 character
- **Format:** String
- **Accepted Value:** Number
- **Device Channel:** 01-APP, 02-BRW

- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** 01-PA: Required, 02-NPA: Conditional
- **Conditional Inclusion:** Required for 02NPA if 3DS Requestor Authentication Indicator = 02 or 03.

- **Field Name:** `messageCategory`

- **Description:** Identifies the category of the message for a specific use case
- **Length:** 2 characters
- **Format:** String
- **Accepted Value:** 01-PA, 02-NPA
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Required

- **Field Name:** `purchaseDate`

- **Description:** Date and time of the purchase, expressed in UTC.
- **Length:** 14 characters
- **Format:** String (Date Format: YYYYMMDDHHMMSS)
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** 1-PA: Required, 02-NPA: Conditional
- **Conditional Inclusion:** Conditional (Required if purchaseAmount is set)

- **Field Name:** `deviceChannel`

- **Description:** Indicates the type of channel interface being used to initiate the transaction.
- **Length:** 2 characters
- **Format:** String
- **Accepted Value:** 01 (APP); 02 (BRW); 03 (3RI)
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA

- **Message Inclusion:** Required
- **Field Name:** `acctNumber`
 - **Description:** Account number that will be used in the authorisation request for payment transactions. It will be represented by PAN, token.
 - **Length:** 13-19 characters, or up to 72 characters when encryption for sensitive data is enabled
 - **Format:** String
 - **Accepted Value:** Format represented ISO 7812.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
 - **Message Inclusion:** Required
- **Field Name:** `merchantName`
 - **Description:** Merchant name assigned by the Acquirer or Payment System.
 - **Length:** Variable, maximum 40 characters
 - **Format:** String
 - **Accepted Value:** Same name used in the authorisation message as defined in ISO 8583.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
 - **Message Inclusion:** 01-PA: Required, 02-NPA: Optional
 - **Conditional Inclusion:** Optional but strongly recommended to include for 02NPA if the merchant is also the 3DS Requestor.
- **Field Name:** `cardHolderInfo`
 - **Description:** Information about the Cardholder, which is provided by the 3DS Requestor. For further details, refer to the [CardHolderInfo Data Elements](#) section
 - **Type:** CardHolderInfo
- **Field Name:** `issuerName`
 - **Description:** Name of the Issuer
 - **Length:** Variable, maximum 64 characters.
 - **Format:** String
 - **Accepted Value:** Any.

- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Required

AdditionalInfo Data Elements

- **Field Name:** `clientId`
 - **Description:** Client ID
 - **Length:** 15 characters
 - **Format:** String
 - **Accepted Value:** Decimal numbers
 - **Message Inclusion:** Optional (this field will be excluded from RESTful JSON message when it has no value)
- **Field Name:** `deviceId`
 - **Description:** Device ID
 - **Length:** Variable, maximum 36 characters
 - **Format:** String
 - **Accepted Value:** Any
 - **Message Inclusion:** Optional (this field will be excluded from RESTful JSON message when it has no value)

CardHolderInfo Data Elements

- **Field Name:** `cardholderName`
 - **Description:** Cardholder name
 - **Length:** 2-45 characters or up to 104 characters when encryption for sensitive data is enabled
 - **Format:** String
 - **Accepted Value:** Alphanumeric special characters, listed in EMVBook 4, "Appendix B".
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA

- **Message Inclusion:** Conditional
- **Conditional Inclusion:** Required unless market or regional mandate restricts sending this information.
- **Field Name:** `email`
 - **Description:** The email address associated with the account that is either entered by the Cardholder, or is on file with the 3DS Requestor.
 - **Length:** 254 characters
 - **Format:** String
 - **Accepted Value:** Shall meet requirements of Section 3.4 of IETF RFC 5322.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
 - **Message Inclusion:** Conditional
 - **Conditional Inclusion:** Required unless market or regional mandate restricts sending this information.
- **Field Name:** `homePhone`
 - **Description:** The home phone number provided by the Cardholder. For further details, refer to the [HomePhone Data Elements](#) section
 - **Type:** HomePhone
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
 - **Message Inclusion:** Conditional
 - **Conditional Inclusion:** Required unless market or regional mandate restricts sending this information.
- **Field Name:** `mobilePhone`
 - **Description:** The mobile phone number provided by the Cardholder. For further details, refer to the [MobilePhone Data Elements](#) section
 - **Type:** MobilePhone
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
 - **Message Inclusion:** Conditional

- **Conditional Inclusion:** Required unless market or regional mandate restricts sending this information.

- **Field Name:** `shipAddrCity`

- **Description:** City portion of the shipping address requested by the Cardholder
- **Length:** Variable, maximum 50 characters
- **Format:** String
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

- **Field Name:** `shipAddrCountry`

- **Description:** Country of the shipping address requested by the Cardholder.
- **Length:** 3 characters
- **Format:** String
- **Accepted Value:** ISO 3166-1 three-digit country code; 901-999 values are excluded and not permitted.
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

- **Field Name:** `shipAddrLine1`

- **Description:** First line of the street address or equivalent local portion of the shipping address requested by the Cardholder.
- **Length:** Variable, maximum 50 characters
- **Format:** String
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

• **Field Name:** `shipAddrLine2`

- **Description:** Second line of the street address or equivalent local portion of the shipping address requested by the Cardholder.
- **Length:** Variable, maximum 50 characters
- **Format:** String
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

• **Field Name:** `shipAddrLine3`

- **Description:** Third line of the street address or equivalent local portion of the shipping address requested by the Cardholder.
- **Length:** Variable, maximum 50 characters
- **Format:** String
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

• **Field Name:** `shipAddrPostCode`

- **Description:** The ZIP or other postal code of the shipping address requested by the Cardholder
- **Length:** Variable, maximum 16 characters
- **Format:** String
- **Accepted Value:**
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional

• **Field Name:** `shipAddrState`

- **Description:** The state or province of the shipping address associated with the card being used for this purchase.

- **Length:** Variable, maximum 3 characters
- **Format:** String
- **Accepted Value:** Should be the country subdivision code defined in ISO 3166-2.
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA
- **Message Inclusion:** Optional
- **Field Name:** `workPhone`
 - **Description:** The work phone number provided by the Cardholder. For further details, refer to the [WorkPhone Data Elements](#) section
 - **Type:** WorkPhone
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
 - **Message Inclusion:** Conditional
 - **Conditional Inclusion:** Required (if available) unless market or regional mandate restricts sending this information.

HomePhone Data Elements

- **Field Name:** `cc`
 - **Description:** Country Code of the number
 - **Length:** 1-3 characters
 - **Format:** String
 - **Accepted Value:** Refer to ITU-E.164 for additional information on format and length.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
- **Field Name:** `subscriber`
 - **Description:** Subscriber sections of the number
 - **Length:** Variable, maximum 15 characters
 - **Format:** String
 - **Accepted Value:** Refer to ITU-E.164 for additional information on format and length.

- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA

MobilePhone Data Elements

- **Field Name:** `cc`
 - **Description:** Country Code of the number
 - **Length:** 1-3 characters
 - **Format:** String
 - **Accepted Value:** Refer to ITU-E.164 for additional information on format and length.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA
- **Field Name:** `subscriber`
 - **Description:** Subscriber sections of the number
 - **Length:** Variable, maximum 15 characters
 - **Format:** String
 - **Accepted Value:** Refer to ITU-E.164 for additional information on format and length.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA

WorkPhone Data Elements

- **Field Name:** `cc`
 - **Description:** Country Code of the number
 - **Length:** 1-3 characters
 - **Format:** String
 - **Accepted Value:** Refer to ITU-E.164 for additional information on format and length.
 - **Device Channel:** 01-APP, 02-BRW, 03-3RI
 - **Message Category:** 01-PA, 02-NPA

• **Field Name:** `subscriber`

- **Description:** Subscriber sections of the number
- **Length:** Variable, maximum 15 characters
- **Format:** String
- **Accepted Value:** Refer to ITU-E.164 for additional information on format and length.
- **Device Channel:** 01-APP, 02-BRW, 03-3RI
- **Message Category:** 01-PA, 02-NPA

OobRequestChallengeResult Data Elements

• **Field Name:** `requestChallengeEnum`

- **Description:** Result of requesting OOB authentication challenge to `OOB-Authenticator-System`, that determines whether OOB authentication method is available for this card or not.
- **Length:**
- **Format:**
- **Accepted Value:** OK, ERROR
- **Accepted Value:**
- **Message Inclusion:** Required

• **Field Name:** `oobTransId`

- **Description:** Unique identifier assigned by the `OOB-Authenticator-System` to identify a single OOB Authentication Challenge.
- **Length:** Variable, maximum 36 characters
- **Format:** String
- **Accepted Value:**
- **Message Inclusion:** Optional

• **Field Name:** `message`

- **Description:** Any required message that should be returned to the `ACS`
- **Length:** Variable, maximum 500 characters
- **Format:** String

- **Accepted Value:**
- **Message Inclusion:** Optional

OobAuthenticationResult Data Elements

- **Field Name:** `authenticationResultEnum`
 - **Description:** Result of OOB authentication challenge
 - **Length:**
 - **Format:**
 - **Accepted Value:** AUTHENTICATED, NOT_AUTHENTICATED, ERROR, PENDING
 - **Message Inclusion:** Required
- **Field Name:** `message`
 - **Description:** Any required message that should be returned to the `ACS`
 - **Length:** Variable, maximum 500 characters
 - **Format:** String
 - **Accepted Value:**
 - **Message Inclusion:** Optional